

**SPECIFICATION**RECEIVED
AUG 21 2002
TECHNOLOGY CENTER 2800**TITLE OF THE INVENTION**

OPTICAL FIBER ARRAY

BACKGROUND OF THE INVENTION**FIELD OF THE INVENTION**

The present invention relates to an optical fiber array having a holding member mounted thereto, and having optical fibers arranged and held within predetermined intervals.

—More particularly, the present invention relates to a technique of preventing release or delamination of the holding member.

DESCRIPTION OF RELATED ART

Conventionally, a fiber array having optical fibers arranged therein and fixed thereto is formed as shown in FIG. 4. In FIG. 4, reference numeral 12 denotes a holding member that consists of a substrate 13 and a cover plate 15. A plurality of V grooves 14 having a V shaped section (housing grooves) are formed at on the substrate ~~12~~. Optical fibers (optical fiber bare portions) 1 are housed in the individual V grooves 14, and an adhesive is filled in the V grooves. Then, the cover plate 15 is positioned on the V grooves ~~covered~~ to pinch the optical fibers 1 between substrate 13 and cover plate 15, and In this manner, the optical fibers 1 are adhered and fixed ~~into~~ in the V grooves 14. In addition, reference numeral 1a denotes a covered portion of the optical fibers, where a plurality of the optical fibers 1a are coupled to one another via a covering ~~with each other~~ to form a fiber ribbon 16.

The holding member 12 is formed by processing a glass plate, for example, ~~and with~~ the V grooves 14 ~~being~~ formed in parallel on a substrate top which is ground to a mirror face. In addition, a space between the adjacent V grooves is small so that an adhesive face is

widely formed at the right and left ends of a bundle of the V grooves in order to ensure adhesion between the substrate 13 and the cover plate 15.

However, the above described fiber array is often placed under severe outdoor severe environments. That is, the fiber array is subject to temperatures ranging from a high temperature of 60 °C to a low temperature of -40 °C, ~~and is~~ Fiber arrays are also subjected to dry, humid and high temperature environments ~~like asuch as desert conditions or the like, and humid high temperature environment.~~ The optical fiber array ~~mustis required to~~ maintain constant and proper performance characteristics under such severe environments for a long durationtime. However, in the case where the above fiber array is subjected to such severe environmental conditions for a long durationtime, there has occurred a phenomenon that the substrate 13 and the cover plate 15 fixing the optical fibers 1 in the V grooves are released or delaminated ~~because of~~ due to environmental variations with an elapse of over time, and This results in the optical fibers arebeing unreliably fixed in the V grooves.

In an optical fiber array, if an optical axis deviates from a predetermined position, aan optical transmission loss is increased between this optical fiber and optical part being optically connected therewith. Thus, a very high position precision of 0.5 microns or less is required to maintain the optical connection. ~~Therefore, if~~ the above release phenomenon occurs, a displacement of the optical fiber occurs, resulting in degraded optical transmission characteristics. In addition, ~~finally,~~ an optical fiber may become detachedslip off from the substrate housing the fiber.

SUMMARY OF THE INVENTION

The present invention has been made in order to solve the foregoing problem. It is an object, therefore, of the present invention to provide an optical fiber array in which the

VERSION WITH MARKINGS TO SHOW CHANGES MADE

Appendix B

release or delamination of the holding member components is not likely to occur ~~toe the like~~ hardly occurs, even under severe environmental conditions, and Thus, proper optical transmission characteristics are maintained because the optical connection, the optical fibers and an optical part is maintained.

In order to solve the foregoing problems, according to a first aspect of the present invention, there is provided an optical fiber array including ~~comprising~~ a holding member that consists of a substrate having forming a sectional V-shaped housing grooves with cross-sectional V shapes formed thereon, for housing an optical fibers on a top face, and a cover plate covering the top face of the substrate, so as to house the A tip, bare portion of the optical fibers are there in, with the bare portion of the optical fiber fixed positioned in the housing grooves and by filling an adhesive is supplied between the substrate and a cover plate so as to fix the optical fibers to in the housing grooves, wherein a A distance M between a center axis of the housing groove that is located at an outermost portion radial position among the housing grooves and an end portion of the substrate is 5 times or more than the radius of the optical fiber, and a A distance Y between the substrate and the cover plate is $L / 6 \leq Y \leq L$, with Y being the thickness of the adhesive layer and L being relevant to a distance L from a contact point P between the housed optical fiber and the housing groove to the cover plate.

According to a second aspect of the present invention, there is provided an optical fiber array according to the first aspect, wherein a height of a site protruding portion of the optical fiber, which protrudes from the upperface of the substrate, ~~of the optical fiber housed in the housing groove~~ is substantially equal to the distance Y between the substrate and the cover plate.

According to a third aspect of the present invention, there is provided an optical fiber array ~~according to the first or second aspect,~~ wherein the distance Y between the substrate and the cover plate is $L / 4 \leq Y \leq L$.

According to a fourth aspect of the present invention, there is provided an optical fiber array ~~according to any of the first to third aspects,~~ wherein the adhesive is epoxy-based.

According to a fifth aspect of the present invention, there is provided an optical fiber array ~~according to any of the first to fourth aspects,~~ wherein the width of the cover plate is different from the width that of the substrate.

According to a sixth aspect of the present invention, there is provided an optical fiber array ~~according to any of the first to fifth aspects,~~ wherein a placement face for placing a covered portion of the optical fiber is provided at the rear part of a housing groove forming face, and a step is provided between the housing groove forming face and the placement face, thereby placing and housing the optical fiber.

The Inventor has ~~found~~discovered the following results through ~~testing~~experimental observations. That is, the above release or delamination is caused by a thin adhesive layer between at the substrate and a cover plate which that spreads ~~to the~~ outside of the outermost portion of at the housing groove. Namely, in the case where a circular optical fiber is housed in a V groove, ~~there occurs contraction in~~ the adhesive is contracted during curing an adhesive which is caused by an adhesive stay portion at the periphery of optical fibers (in the housing groove); Also, there is a difference in thermal expansion rates between the adhesive and the substrate or between the adhesive and the cover plate. Alternatively, increasingincreased humidity tends to causes expansion of ~~the~~ adhesive materials. AndAccordingly, the stress ~~concentration of the adhesive~~ which is likely to concentrate in

portions of the V groove caused by these~~the above~~ phenomena cannot be sufficiently prevented ~~throughby~~ the used of a thin adhesive layer.

A fiber array is fixed between a substrate and cover plate through the use of~~mounted~~ by an adhesive, and also tends to be~~is~~ formed in its complicated shapes. Thus, there exists a variety of stresses which are likely to occur in the fiber array, such as partial or isolated strong stresses or a condition of general~~entire~~ stress between the substrate and the cover plate. The partial or isolated stress tends to occurs at a resin stay portion ~~such as~~along the periphery of the fibers fixed in a V groove, as described above. This is believed to be due to a mechanism in which the stress of the adhesive stay portion indicated by A shown in FIG. 5 is applied or transferred to a portion indicated by B₂, and ~~if~~ the adhesive layer of this portion B is thin, ~~this~~the stress at this position cannot be absorbed, and a release or delamination between the substrate and cover plate occurs ~~with the~~ portion of B.

For example, if a release or delamination occurs ~~with~~at a portion of the fiber array, such as portion B, the entire stress is applied or transferred to this portion ~~or~~and water is prone to ~~invades the~~this release portion, which exacerbates the problem and causes~~whereby~~ ~~such release is further~~ separation or release at portion B~~expanded.~~

~~The above construction~~present invention is provided in response to ~~such action~~the above-discussed problems of prior art adhesive layers, ~~whereby~~ The adhesive layer of the present invention can absorb the stress ~~concentration~~concentrated at the above-discussed portions of the substrate, and a release of the optical fiber~~is unlikely to occur~~ between the ~~optical fiber and~~the substrate is not likely to occur, ~~or fixed substrate~~ even under use in severe environments. ~~Then~~Thus, proper optical characteristics can be maintained.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice

VERSION WITH MARKINGS TO SHOW CHANGES MADE
Appendix B

of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the present invention and, together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principle of the present invention, in which:

FIG. 1 is an enlarged sectional view of an optical fiber array in accordance with showing an example according to the preferred embodiments of the present invention;

FIG. 2A ~~to (a)-~~ FIG. 2H ~~(h)~~ are photographs showing for explaining how a changes in fiber array adhesive portions is changed due to environmental testing conditions, wherein FIGS. 2(a)-(d) ~~A to FIG. 2D~~ each show a construction of are fiber arrays in accordance with the present invention compared to; FIGS. 2(e)-(h), ~~E to FIG. 2H~~ which each shows a conventional fiber array construction;

FIG. 3 is an illustrative view of a holding member in accordance with the present invention as seen used in environment testing shown in FIG. 2;

FIG. 4 is a perspective view of ~~an~~ a conventional optical fiber array;

FIG. 5 is an enlarged sectional view illustrating one fiber portion seenshown in FIG. 4;

FIG. 6(a)-A to FIG. 6(c) ~~C~~ each show ~~how is an~~ adhesive layer ends of ~~an~~ optical fiber arrays, wherein where FIG. 6(a) ~~A~~ is shows a sectional view illustrating in accordance with the present invention, FIG. 6(b) ~~B~~ is shows a sectional view illustrating in accordance with another example of the present invention, and FIG. 6(c) ~~C~~ is shows a sectional view illustrating a conventional fiber array example; and

VERSION WITH MARKINGS TO SHOW CHANGES MADE
Appendix B

~~FIGS. 7(a)A and FIG. 7(b)B show side views of a construction of a V groove rear ends of the optical fiber arrays, wherein~~ FIG. 7(a)A is an illustrative shows a side view of essential parts according to the present invention, and FIG. 7(b)B is an illustrative shows a side view of conventional essential parts of a conventional fiber array; ~~wherein reference numeral 1 denotes an optical fiber, reference numeral 2 denotes a holding member, reference numeral 3 denotes a substrate, reference numeral 3a denotes a step, reference numeral 4 denotes a V groove, reference numeral 5 denotes a cover plate, reference numeral 6 denotes an adhesive layer, reference numeral 6a denotes an adhesive, reference code L denotes a distance from a contact point between a V groove and an optical fiber to a cover plate, reference code M denotes a distance from a center of a housing groove at the outer most portion of the substrate to a substrate end, reference code P denotes a contact point between a V groove and an optical fiber, and Y denotes thickness of an adhesive layer.~~

DETAILED DESCRIPTION OF THE INVENTION EMBODIMENT

Reference will now be made in detail to the presently preferred embodiments of the invention as illustrated in the accompanying drawings, in which like reference numerals designate like or corresponding parts.

~~Hereinafter, preferred embodiments of the present invention will be described in detail with reference to the accompanying drawings.~~

—FIG. 1 is an enlarged sectional view of an optical fiber array according to the present invention, ~~wherein~~ in which; reference numeral 1 denotes an optical fiber (a bare optical fiber); reference numeral 2 denotes a holding member that consists of a substrate 3 and a cover plate 5; a V groove 4 is formed at ~~on~~ the substrate 3; and an optical fiber 1 is housed in the V groove 4. In addition, an adhesive 6a is filled between the substrate 3 and cover plate 5 ~~at~~ along the periphery of the optical fiber 1, ~~and between the substrate 3 and the cover plate 5.~~

VERSION WITH MARKINGS TO SHOW CHANGES MADE

Appendix B

An opening angle of the V groove 4 is 70 degrees, for example, and ~~the~~ The optical fiber 1 is formed to be 62.5 microns in radius, for example.

The V groove 4 is formed ~~so~~such that a part of the optical fiber 1, being housed therein, is slightly protruded from the upper face of the substrate 3, and ~~is formed so that~~ ~~the~~ the protrusion length of the optical fiber is substantially equal to the thickness of the adhesive layer 6 formed between the substrate 3 and the cover plate 5. In addition, a distance M between the center of the housing groove at the outer most portion of the substrate 3 and the substrate end (shown in FIG. 3) is 5 times or more of the optical fiber radius relevant to the radium R of the optical fiber 1.

Then, the thickness Y of this adhesive layer 6 is defined as follows, ~~when a distance~~ ~~L, from which is~~ a contact point P between the V groove 4 and the optical fiber 1 to the cover plate 5 is: ~~defined as a reference.~~

$$L / 6 \leq Y \leq L \dots (\text{Range 1})$$

If ~~the~~ the thickness Y of the adhesive layer 6 ~~is defined~~exists in the above defined range, ~~whereby~~ as shown in the test results described later, the adhesive layer 6 sufficiently absorbs a-stresses generated from the contraction ~~generated while~~of the adhesive is ~~cured or~~during curing. In addition, adhesive layer 6 sufficiently absorbs stresses generated by a difference in thermal expansion rate ~~or expansion rate~~ between the substrate 3 and the cover plate 5 ~~so~~such that alignment of the optical fiber ~~constant characteristics~~ can be maintained without being released from the V grooves, even under severe environmental conditions.

In addition, from the viewpoint of adhesives, the stress caused by the adhesive

increases particularly with adhesives having a higher Young's Modulus ~~of the adhesive~~. For example, in the case where an epoxy based adhesive is employed, the Young's Modulus is generally high as compared with an acryl based or silicon based adhesive. Thus, the stress is also increased, and the adhesive layer structure of the present application is effective. In particular, when an epoxy based adhesive ~~of~~having Young's Modulus not less than 2 kgf / mm² is used, the stress is particularly increased. Thus, the adhesive layer structure of the present application is effective.

The adhesive used ~~herein the present invention~~ denotes one which is used for adhering and bonding ~~of at least V-groove periphery (adhering and bonding of the an outer peripheral surface of a bare optical fiber, cover plate and substrate)~~. In addition, in order for the optical fiber 1 to come into reliable two point contact with the inclined face of the V groove 4, it is preferable that a ~~realistic~~ contact point is moved upwardly with a margin of about 10 microns from a theoretical contact point in consideration of processing precision or measurement precision. In this case, the above (range 1) is $(L - 10 \text{ microns}) / 6 \leq Y \leq (L - 10 \text{ microns})$.

Table 1 compares changes of the adhesive portion of the fiber array ~~when during~~ environmental testing (boiling test), ~~is carried out by~~ As is shown in Table 1, at the fiber arrays ~~created by changing~~ were produced to have varying thicknesses Y of the adhesive layer δ , ~~where~~ The fiber arrays ~~is~~were soaked in boiling water to investigate an ~~occurrence of~~ whether the release or delamination of the holding member occurred after a predetermined time ~~has~~had elapsed. In the ~~Table 1~~, O denotes a good state in which no release of optical fibers ~~has~~ occurred, Δ denotes a state in which partial release of the optical fibers ~~has~~ occurred, and X denotes a state in which an extensive release of the optical fibers ~~has~~ occurred.

Table 1

Thickness of adhesive layer Y	Boiling time			
	15hr	36hr	60hr	
L/2	○	○	○	Photograph
L/4	○	○	○	
L/6	○	○	△	
L/8	×	×	×	Photograph

FIGS. 2(a)-(h)A to FIG. 2H are show photographs illustrating the changes to the ~~for~~ explaining how an optional optical fiber array adhering portion is changed due to the due to the above environmental tests shown in Table 1, wherein FIG. 2(a)- 2(d)A to FIG. 2D are photographs of $Y = L / 2$ shown in Table 1, and FIG. 2(e)-2(h)E to FIG. 2H are photographs of $Y = L / 8$ in a conventional optical fiber array example. In addition, the holding member 32 of the optical fiber array taken as each of the photographs shown in FIG. 2 is schematically shown in FIG. 3.

FIG. 3 is a plan view of the holding member. As shown in the figure, the holding member 2 used in the ~~provided for~~ environmental tests illustrated in Table 1 has three groups of housing grooves, each consisting of eight grooves positioned on substrate 3. An ~~optical fiber array is formed in such a way that~~ The optical fibers 1 are positioned on the V grooves of substrate 3 ~~housed in the holding member 2~~, adhesive is applied thereon, and then, the cover plate 5 is positioned on the optical fibers adhered. The ~~protrusion quantity~~ part of the optical fiber 1 that protrudes from the substrate (i.e., extending above a plane parallel to top surface

of the V grooves) is ~~varied~~^{changed} by changing the ~~size~~^{angles} of the V grooves. ~~so that This~~
~~also functions to adjust the thickness Y of the adhesive is set to its~~^{a desired thickness.}

In FIG. 2, although there is no change ~~at the~~^{after} 60-hour boiling ~~point~~^{in the left}
 photographs ~~A to D~~^{2(a)-(d)}, it is ~~possible to verify that~~^{there occurs a spot-like pattern on}
 main adhesive faces 8, 8 (~~shown schematically in Fig. 3~~) ~~of the left and right of the substrate~~
 after 15 hours ~~or more of boiling and on in the right~~^{in photographs E to H}~~2(e)-(h).~~^{and}
 Additionally, a portion in a different state from a state before boiled occurs between the
 optional fiber groups as well. These sites are where adhesive has been released. From these
 photographs, in the case where ~~the right side, i.e.,~~^{the thickness Y of the adhesive layer is $L / 8$} ,
 it is found ~~that release has already occurred after 15 hours of boiling.~~^{That is, when the left}
~~side, i.e., thickness Y of the substrate is $L / 2$, no release occurs even after 60 hours of~~
 boiling.

Thus, from the test results shown in Table 1, it can be judged that, as long as a
 distance between the center axis of the housing groove at the outermost portion of the
housing grooves and the substrate end is 5 times or more of the optical fiber radius; and the
 adhesive layer thickness Y is $L / 6$ or more, ~~the release of adhesive is unlikely to~~^{hardly}
 occurs, and the optical fiber array can be used even under severe environments. Further, if
 the adhesive layer thickness Y is $L / 4$ or more, it can be judged that no release of adhesive
 occurs, and a good bonding state can be continuously maintained.

In the meantime, the optical fiber array is generally formed so that the fibers are
 pressed in the substrate V groove 4 by the cover plate 5. Although optical grinding is applied
 to the tip end face of the optical fiber array, the fiber end face is required to be set to a desired
 angle. Thus, in general, grinding is performed when a side face parallel to the V groove 4 is
 defined as a reference during grinding. At this time, although the side face of the substrate 3

VERSION WITH MARKINGS TO SHOW CHANGES MADE
Appendix B

can be easily processed so as to be parallel to the V groove 4, the cover plate 5 is merely loaded on the optical fibers 1. Thus, it is not easy that the side face of the cover plate 5 is parallel to the optical fibers 1.

Therefore, it is natural that the grinding standard face is on the side face of the substrate 3 so that the cover plate 5 should not be at the outside of the right and left of the substrate 3 in order to ensure this state. As a measure, the width of the cover plate 5 is made smaller than that of the substrate 3, whereby slight displacement can be permitted, thus making it possible to apply the cover.

In this case, as shown in FIG. 6 ~~that is the sectional view illustrating the optical fiber array~~, the adhesive 6a is pooled at a stepped portion C in a meniscus manner, which provides an effect of increasing adhesive force. However, in the case where the adhesive layer is thin, ~~the stresses occurring at stepped portion C caused here results in an occurrence of the release of the adhesive layer~~ (the mechanism in which a release occurs is similar to that occurring in the V grooves). In particular, this site is situated at the outside of the substrate, and is subjected to open air. Thus, if a release of adhesive occurs, it permits moisture to easily invade the interior of the substrate, which, in turn, accelerates the progress of adhesive release.

~~In this manner, this site~~ As can be understood from the above, stepped portion C is an important portion that prevents a release of adhesive. As shown in FIG. 1, as long as a large adhesive layer is ensured, ~~the stress does not concentrate, and a release is unlikely to occur hardly occurs.~~ Thus, ~~the construction according to the present invention makes it possible to~~ ensure high reliability in the same manner as ~~that employed for the V groove portion.~~

FIG. 6(a)A is a sectional view illustrating an optical fiber array according to the present invention, and FIG. 6(c)C is a sectional view illustrating a conventional optical fiber array.

As shown in FIG. 6(b)B, even if the width of the cover plate 5 is greater than that of the substrate 3, a meniscus-like pool portion is formed at the stepped portion C. The construction of the present invention, i.e., a large adhesive layer is ensured, whereby the stress does not concentrate, a release does not occur, and high reliability can be ensured in the same manner as the V groove portion. However, as described above, the end face of the optical fiber array is hardly ground precisely, and thus, the cover plate width is preferably formed to be smaller than the substrate ~~in~~-width.

Figs. 7(a)-7(b) show side views of V groove rear ends in accordance with the present invention and a conventional fiber array, in which: reference numeral 1 denotes an optical fiber; reference numeral 3 denotes a substrate; reference numeral 3a denotes a step; reference numeral 5 denotes a cover plate; and reference numeral 6a denotes an adhesive layer.

With respect to stepped portion 3a, optical fibers are easily damaged by an edge of the step. In the case where a release occurs, even partially, at stepped portion 3a, there is an apprehension that the damage of the fiber due to the step is further accelerated by the function of stress. Thus, it is very important that no release of adhesive occurs at stepped portion 3a.

As shown in FIG. 7(a)A ~~that is a view illustrating a side face of the optical fiber array,~~ in the case where a step 3a is provided at the rear end of a V groove, which in order functions to reduce the concentration of the stress applied to the tip end of the optical fiber, and a cover portion mount face is provided at the rear part of the substrate by one stage lower than a V groove forming face, a large amount of adhesive 6a exists in ~~this~~ step 3a. Thus, the stress at this portion, which is caused by the adhesive, ~~concentrates on~~ is concentrated in the adhesive

layer 6 between the substrate 3 and the cover plate 5. In the case of such structure ~~as well,~~
~~this construction~~ the present invention is particularly effective.

Further, as shown in FIG. 7(a) ~~A, although R a taper is preferably~~ is provided at the end
 at the substrate side of the cover plate 5, ~~a taper or R is preferably applied to the substrate~~
~~side in this manner~~ in order to reduce the stress more significantly. Namely, a large
~~amount~~ the thickness of the adhesive layer ~~thickness~~ is made gradually closer to the adhesive
 thickness Y, whereby the stress concentration can be further prevented.

~~With respect to this stepped portion, an optical fiber is easily damaged by an edge of~~
~~the step. In the case where a release occurs even partially at this portion, there is~~
~~apprehension that the damage of the fiber due to the step is further accelerated by the function~~
~~of stress. Thus, it is very important that this portion is prevented from a release.~~

In addition, in the above embodiments, when the optical fibers are fixed by being
~~pinched~~ pinching them between the substrate 3 and the cover plate 5, the cover plate is abutted
 against the optical fibers so such that the thickness of the adhesive layer is equal to the height
 of the ~~protrusion~~ portion of the optical fibers which protrude from the V grooves on the
 substrate, ~~of the optical fibers.~~ However, as long as the optical fibers securely come into
 contact with a V groove at two points, it may not be necessary to abut the cover plate ~~may not~~
~~be abutted with a portion of the optical fibers.~~ Further, although a plurality of V grooves are
generally provided on the substrate, even if one V groove exists, an adhesive layer is can be
 formed as described above, ~~whereby~~ and good optical coupling characteristics can be
 maintained.

(Advantageous Effect of the Invention)

As has been described above in detail, according ~~to the invention~~ according to the first
 to fourth aspects of the invention, even under severe environments, a release hardly occurs

VERSION WITH MARKINGS TO SHOW CHANGES MADE
Appendix B

between the optical fiber and the substrate or fixed substrate, and good optical characteristics can be maintained.

According to the fifth aspect of the ~~present~~ invention, in addition to the advantageous effects of any one of the first to fourth aspects, the width of the cover plate is different from ~~that~~ the width of the substrate. Thus, a meniscus-like adhesive pool portion is formed, ~~and~~ which increases adhesive forces ~~increases~~.

According to the sixth aspect of the ~~present~~ invention, in addition to the advantageous effects of any one of the first to fifth aspects, the stress applied to the tip end of the optical fiber is reduced, and a release hardly occurs.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspect is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.